



DEFA Power™

Item.no: 715000

DEFA Power™

Smart EV Charging Station with integrated charging cable. Max 22kW, 32A

The smartest way to control your power, allowing you to charge at the lowest cost with the maximum output. DEFA Power has an intuitive display and 6 meter integrated charging cable that simplifies your daily use and gives you full control of your charging. DEFA Power optimizes available power, and with PowerSmart you can avoid peak periods and charging when power is most expensive.

DEFA Power – more power to you!

Made for maximum power

True 22kW charging.
DEFA Power is designed through advanced simulations ensuring fastest possible charging.

PowerSmart™ with the Power App

The power to set your charge when the prices are low, based on daily prices from Nord Pool. You can also avoid extra tariffs on peak periods. Can be used with any energy company and all cars.

User-friendly

Intuitive high quality display with step by step charging experience.

Future ready

Connectivity: WiFi, 4/5G, LAN
Configuration: Bluetooth
Open standard: OCPP 2.0.1 and ISO15118



Easy access

Effective access steering.
- Access control via QR-code
- RFID / NFC, and SMS

Integrated charging cable

Robust 6 meter charging cable made for extreme condition provides flexibility for daily use. Includes a smart vehicle plug cap to protect the connector.


One device fits all

Can handle all power and phase needs in all European markets.

Optimize utilization of available power by upgrading with **DEFA Balancer™**

Specification

Dimension:



General:


Item number: 715000
E-number: 1500189 (Norway)
EAN: 7042287150002
Dimension (mm): L: 350 x W: 167 x D: 113
Weight unit: 2,5 kg
Weight cable: 3,5 kg
Operating temperature: -40°C to +50°C
Storage temperature: -50°C to +85°C
Material charging unit: Plastic

Charging:

Charging power: Up to 22kW
Charging current: 6–32A (adjustable)
Voltage: 230/400 V (1/3-phase, 50-60Hz)
Charging mode: Mode3
Connection to vehicle: Type 2
Charging cable: Included, 6 m

Interface:

Integrated display
Size: 69 mm x 69 mm
Brightness: Automatically adjusted
Power setup: App to set DEFA Power



Specification

Safety & protection:

IP: 55
IK: 10
Fire classification: UL94 V0
Isolation class: I
Overvoltage category: III
Overheat protection: Internal sensor

Standard & certification:

CE
IEC 61851-1
IEC 61439-7 ACSEV
IEC 62955

Connection:

Grid: TN / IT / TT
Fuse size: 40A
Short-circuit current: 10kA
RCD: 30mA AC and 6mA DC
Maximum cable size: 16 mm²
Torque value: 2,5Nm
Stripping length: 20 mm +/-2

Warranty:


5 years (Norway)

Recycling:


EE-waste

Included:

Charging station with
6 m charging cable



Wall
bracket



Cable
clip



Tools &
screws/plugs

